



* Referential photo



Fiorella Representaciones S.A.C. Importador y distribuidor autorizado de bridas FR para Perú y para su exportación.

Dimensions are in mm

Nominal Pipe Size, NPS		Outside Diameter of Flange (O)	Minimum Thickness of Flange, (t _f)	Diameter of Hub (X)	Length Through Hub (Y)	Bore Minimum (B)	Groove Number	Pitch Diameter (P)	Deep (E) [Note (1)]	Width (F)	Radius at Bottom (R)	Diameter of Raised Portion (K)	Diameter of Bolt Circle (W)	Number of Bolts
inch	mm													
1"	25	110	12.7	49	16	34.5	15	47.63	6.35	8.74	0.8	63.5	79.4	4
1 1/4"	31	115	14.3	59	19	43.2	17	57.15	6.35	8.74	0.8	73.0	88.9	4
1 1/2"	38	125	15.9	65	21	49.5	19	65.07	6.35	8.74	0.8	82.5	98.4	4
2"	50	150	17.5	78	24	61.9	22	82.55	6.35	8.74	0.8	102	120.7	4
2 1/2"	63	180	20.7	90	27	74.6	25	101.60	6.35	8.74	0.8	121	139.7	4
3"	75	190	22.3	108	29	90.7	29	114.30	6.35	8.74	0.8	133	152.4	4
3 1/2"	88	215	22.3	122	30	103.4	33	131.78	6.35	8.74	0.8	154	177.8	8
4"	100	230	22.3	135	32	116.1	36	149.23	6.35	8.74	0.8	171	190.5	8
5"	125	255	22.3	164	35	143.8	40	171.45	6.35	8.74	0.8	194	215.9	8
6"	150	280	23.9	192	38	170.7	43	193.68	6.35	8.74	0.8	219	241.3	8
8"	200	345	27.0	246	43	221.5	48	247.65	6.35	8.74	0.8	273	298.5	8
10"	250	405	28.6	305	48	276.2	52	304.80	6.35	8.74	0.8	330	362.0	12
12"	300	485	30.2	365	54	327.0	56	381.00	6.35	8.74	0.8	406	431.8	12
14"	350	535	33.4	400	56	359.2	59	396.88	6.35	8.74	0.8	425	476.3	12
16"	400	595	35.0	457	62	410.5	64	454.03	6.35	8.74	0.8	483	539.8	16
18"	450	635	38.1	505	67	461.8	68	517.53	6.35	8.74	0.8	546	577.9	16
20"	500	700	41.3	559	71	513.1	72	558.80	6.35	8.74	0.8	597	635.0	20
22"	550	750	44.5	610	78	564.4	80	615.95	6.35	8.74	0.8	648	692.2	20
24"	600	815	46.1	663	81	616.0	76	673.10	6.35	8.74	0.8	711	749.3	20

MAC - MMXXIV

* Note : Dimensions, design and materials are subject to change without notice. Reference weights

