Technical Data



Performance you can trust



FOODLUBE® Dismantling Spray



Food grade penetrating spray for effective release

Product Overview

ROCOL® FOODLUBE Dismantling Spray is a non-toxic, fast acting, penetrating lubricant which also provides short term corrosion protection for corroded threaded fasteners and other seized components.

ROCOL FOODLUBE Dismantling Spray is NSF H1 registered for incidental contact with food making it ideal for use in food, pharmaceutical and other clean industries where a non-toxic product is required or preferred.

Features and Benefits

- FOODLUBE Dismantling Spray has metal detectable plastic components (aerosol caps and actuators) capable of detection by most metal detection equipment.
- FOODLUBE Dismantling Spray has a wide operating temperature range from -20°C to +110°C.
- FOODLUBE Dismantling Spray provides excellent penetration of rust, scale, grease and general dirt and grime.
- Its fast acting formula provides quick effective release of seized and corroded threaded fasteners.
- FOODLUBE Dismantling Spray leaves a protective film which provides short term corrosion protection.

Directions for Storage and Use

- Shake aerosol well before use.
- Test compatibility with plastics and rubbers and painted or coated surfaces prior to application.
- Hold can upright and apply from a distance of 15 30 cm, coating the components thoroughly and paying particular attention to the seized contact areas.
- In severe cases, applying the product for a second time after several minutes may be beneficial.
- Use only in well ventilated areas and do not apply to very hot surfaces.
- Store below +50°C, out of direct sunlight.
- Shelf life is 5 years from date of manufacture.
- Consult safety data sheet before use.

Specifications

- FOODLUBE Dismantling Spray does not contain: mineral hydrocarbons, animal derived materials, nut oils or genetically modified ingredients.
- FOODLUBE Dismantling Spray is manufactured from only FDA listed ingredients:
 - o FDA Group 21 CFR 178.3570
- FOODLUBE Dismantling Spray is NSF registered:
 - NSF H1 registered 121617
- ISO 21469 certified

Pack Sizes

Pack Size	Part Code
300ml	15720

T +44 (0) 113 232 2600 F +44 (0) 113 232 2740 E customer-service@rocol.com www.rocol.com

ROCOL House, Swillington, Leeds LS26 8BS
Registered Company No. 559693 VAT No. 742 0531 67





ROCOL A division of TW Ltd





Technical Data



Performance you can trust





FOODLUBE® Dismantling Spray

Food grade penetrating spray for effective release

Property	Test Method	Result
Appearance – applied film	Visual	Thin colourless film
Base Type	N/A	Blend of esters
Solvent	N/A	None
Propellant	N/A	CO ₂ (carbon dioxide)
Odour	N/A	Characteristic
Temperature range	N/A	-20°C to +110°C
Density (kg/m³)	N/A	<1
Flash Point (°C)	ASTM D93	>140°C
Water Solubility	N/A	Not miscible
Metal Detection:		
Aerosol Cap	Equivalent sphere size	>3.0mm
Actuator	Equivalent sphere size	>3.0mm

Values quoted above are typical and do not constitute a specification.

Safety Data Sheets

Safety data sheets are available for download from our website www.rocol.com or may be obtained from your usual ROCOL contact.

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility. Issue: 3 Date: 03-13

T +44 (0) 113 232 2600 F +44 (0) 113 232 2740

E customer-service@rocol.com

www.rocol.com

ROCOL House, Swillington, Leeds LS26 8BS Registered Company No. 559693 VAT No. 742 0531 67

Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL



ROCOL A division of TW Ltd



