

Performance you can trust

RS7 SPRAY Non-Silicone Wet Film Mould Release Agent

RS7 Spray is designed to give fast, efficient clean release in critical moulding applications. It penetrates and spreads to all parts of the most intricate mould to give full, clean release, with improved gloss finish.

RS7 Spray is for use where neither silicone nor PTFE derivatives are acceptable. The applied film can be easily removed by most common solvents and is suitable for moulding of parts which will subsequently be over printed or painted. Ideal for use with most types of plastics and rubbers and of particular benefit when used with polypropylene, expanded polystyrene, nylon A100 and nitrile rubbers.

Features

- Effective release of plastics and rubber moulded parts.
- Heat resistant wet film - up to 150°C.
- Gives improved gloss finish.
- Particularly suited to delicate or intricate parts.

Directions for Use

Shake well, hold upright and spray from a distance of approximately 15-30cm (6-12 inches). One pass usually provides sufficient coating. Ensure adequate ventilation. Do not spray onto naked flame or any incandescent material.

NB. Test compatibility with painted or coated surfaces, plastics and rubbers prior to application.

T +44 (0) 113 232 2600
F +44 (0) 113 232 2740
E customer-service@rocol.com

ROCOL A division of **ITW** Ltd

www.rocol.com

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67

Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL



BS EN ISO 9001
Certificate No. FM 12448

BS EN ISO 14001
Certificate No. EMS 67596

OHSAS 18001
Certificate No. OHS 78173



INVESTOR IN PEOPLE

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

PR SPRAY

Propellant	Hydrocarbon blend
Solvent	Isoparaffinic Hydrocarbon
Base Fluid	Blend of silicone oils
Colour	Colourless
Temperature Range	Up to +200°C
Storage	Storage temperature should be kept below 50°C. Storage area should be out of direct sunlight.
Pack Sizes – Part Codes	400ml - 72015

Date: Jan-09

T +44 (0) 113 232 2600
F +44 (0) 113 232 2740
E customer-service@rocol.com

ROCOL A division of **ITW** Ltd

www.rocol.com

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67

Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL



BS EN ISO 9001
Certificate No. FM 12448

BS EN ISO 14001
Certificate No. EMS 67596

OHSAS 18001
Certificate No. OHS 78173

INVESTOR IN PEOPLE

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.