



NPS 1/2 to 3 Only



Machine Bolt With Nuts



Stud Bolts With Nuts

Point height

(Note 1)

Note 1: The length of the stud bolt does not include the height of the points

\* Referential photo

Fiorella Representaciones S.A.C. Importador y distribuidor autorizado de bridas FR para Perú y para su exportación.

Dimensions are in mm

Nominal Pipe Size, NPS		Outside Diameter of Flange (O)	Minimum Thickness of Flange, (t <sub>f</sub> )	Diameter of Hub (X)	Length Through Hub (Y)	Bore Minimum (B)	Bore (B) [Note 2]	Depth of Socket (D)	Diameter of Bolt Circle (W)	Diameter of Bolt Holes (inch)	Number of Bolts	Diameter of Bolts (inch)	Length of Bolts (L)			Weight Approx. (kg)
													Stud Bolts		Machine Bolts	
inch	mm												2mm Raised Face	Ring Joint	2mm Raised Face	
1/2"	12	90	9.6	30	14	22.2	15.8	10	60.3	5/8	4	1/2	55	...	50	0.47
3/4"	18	100	11.2	38	14	27.7	20.9	11	69.9	5/8	4	1/2	65	...	50	0.59
1"	25	110	12.7	49	16	34.5	26.6	13	79.4	5/8	4	1/2	65	75	55	0.87
1 1/4"	31	115	14.3	59	19	43.2	35.1	14	88.9	5/8	4	1/2	70	85	55	1.11
1 1/2"	38	125	15.9	65	21	49.5	40.9	16	98.4	5/8	4	1/2	70	85	65	1.45
2"	50	150	17.5	78	24	61.9	52.5	17	120.7	3/4	4	5/8	85	95	70	2.33
2 1/2"	63	180	20.7	90	27	74.6	62.7	19	139.7	3/4	4	5/8	90	100	75	3.55
3"	75	190	22.3	108	29	90.7	77.9	21	152.4	3/4	4	5/8	90	100	75	4.02
3 1/2"	88	215	22.3	122	30	103.4	90.1	---	177.8	3/4	8	5/8	90	100	75	-
4"	100	230	22.3	135	32	116.1	102.3	---	190.5	3/4	8	5/8	90	100	75	5.99
5"	125	255	22.3	164	35	143.8	128.2	---	215.9	7/8	8	3/4	95	110	85	6.68
6"	150	280	23.9	192	38	170.7	154.1	---	241.3	7/8	8	3/4	100	115	85	7.99
8"	200	345	27.0	246	43	221.5	202.7	---	298.5	7/8	8	3/4	110	120	90	13.29
10"	250	405	28.6	305	48	276.2	254.6	---	362.0	1	12	7/8	115	125	100	19.50
12"	300	485	30.2	365	54	327.0	304.8	---	431.8	1	12	7/8	120	135	100	29.03
14"	350	535	33.4	400	56	359.2	[Note 3]	---	476.3	1 1/8	12	1	135	145	115	38.56
16"	400	595	35.0	457	62	410.5	[Note 3]	---	539.8	1 1/8	16	1	135	145	115	44.49
18"	450	635	38.1	505	67	461.8	[Note 3]	---	577.9	1 1/4	16	1 1/8	145	160	125	54.43
20"	500	700	41.3	559	71	513.1	[Note 3]	---	635.0	1 1/4	20	1 1/8	160	170	140	70.31
22"	550	750	44.5	610	78	564.4	[Note 3]	---	692.2	1 3/8	20	1 1/4	170	185	150	-
24"	600	815	46.1	663	81	616.0	[Note 3]	---	749.3	1 3/8	20	1 1/4	170	185	150	95.25

Note (1) This dimension is for large end of hub, which may be straight or tapered. Taper shall not exceed 7 deg on threaded, slip-on, socket-welding, and lapped flanges. This dimension is defined as the diameter at the intersection between the hub taper and back face of the flange.

Note (2) Dimensions in Column 13 correspond to the inside diameters of pipe as given in ASME B36.10M for standard wall pipe. Thickness of standard wall is the same as Schedule 40 in sizes NPS 10 and smaller. Tolerances in para. 7.5.2 apply. These bore sizes are furnished unless otherwise specified by the purchaser.

Note (3) To be specified by the purchaser.

\* Note : Dimensions, design and materials are subject to change without notice. Reference weights